

MASTER CHEMICALS TECHNOLOGY

MC-CURO 200

Concrete Curing Sealing& Coating Compound

Description:

MC-Curo 200 is a special rubber polymeric material used as curing and sealing compound. It meets the requirements of ASTM C 309-81 type 2 class B "Specification for liquid Membrane forming compound for curing Concrete"

Uses:

MC-Curo 200 is used as:

- ♦ Curing compound for protection fresh concrete against evaporation
- Sealer material on existing plain concrete floors.
- Concrete coating over the cementiciuos concrete floor hardeners .

Where to Use:

MC- Curo 200 is used as a curing and sealing compound on large horizontal or inclined surfaces, such as:

- ♦ Airfields & Highways
- ♦ Pavements walls & dams
- Bridges & foundation slabs
- Other concrete surfaces.

Advantages:

MC-Curo 200 is used on plain concrete surface

- ♦ It may be applied to horizontal or vertical surfaces, smooth or textured indoors or outdoors.
- It is used as a sealer to reduce dusting and make sweeping and cleaning easier.
- Protect fresh concrete against evaporation, keeping good mechanical properties and less shrinkage.

Technical Data:

Appearance : Clear liquid and available in high rang of colors

Specific gravity : $1.16 \pm 0.02 \text{ g/cm}^3 \text{ at } 25 \text{ }^5\text{C}$

Drying time : Quick drying occurs in areas exposed to wind

excessive heat, sun, etc.

Temperature of application : above $+ 5^{\circ}$ C Consumption : about $4-6 \text{ m}^2/\text{L}$.

Shelf life : one year in tightly closed containers

Packaging : 210 liters.

Application:

Surface preparation

MC-Curo 200 is applied immediately after the exposed surface has hardened. If the concrete has lost some of its greenness dampen the surface first with water before applying MC-Curo 200, note that the surface is free of standing water, and do not apply MC-Curo 200 while free water remains on.

Method of application

MC-Curo 200 is applied by spray to the freshly poured concrete using a garden-type spray or an industry sprayer

- ◆ Also MC- Curo 200 can be applied using roller, if the rolling action start to create tiny bubbles on the surface, slow down the rolling motion.
- ♦ Do not "pull" the material when applying
- If second thin application for aesthetic purposed is required, the first coat must be thorough dry before the second coat is applied.

Cleaning

Clean spraying equipment or roller with a suitable thinner

Safety precautions

- ♦ MC-Curo 200 is combustible therefore keep it away from spark and flame.
- Take precautions to prevent material entering the eyes.
- ◆ Take precautions to avoid skin contact.

For more details contact Master Chemicals Technology technical department

Or visit our website www.mc.com.eg

Mob: 01001615868