

MASTER CHEMICALS TECHNOLOGY

MC-Tile Weld

Adhesive Mortar and Grouting for floor tiling

Description:

MC – **Tile Weld** is sand – cement based powder blended with special balaced additives and modified with synthetic resins, ready to use after mixing with water.

Uses:

MC - Tile Weld is used as adhesive for :

- Tile fixing for external and internal floors and walls.
- Plaster board fixing, without preparation.
- Ceramic and mosaic.

Advantages:

- ♦ Quick setting by thin bed method .
- ♦ Strong adhesion .
- ♦ No tile sag.
- ◆ Water resistant (can be used for swimming pools).
- Easy to use.

Technical Data:

Color : grey or white powder

Density :1.6 gm/ cm³
Working time :30-40 min .
Available time for adjusting tiles :10-15 min.

Mixing :25kg powder : 8 ± 0.5 liter of water

Consumption for tiling :Approx 1.1 : $1.5 \text{ kg}/\text{m}^2$

(Rought substrates will increase consumption by 20 to 50 %)

for Grouting :600 gm /m²(20 × 20cm tiles & 0.6×0.6 cm joints

Shelf life :12 months under dry storage conditions in closed bags

Packaging :25 kg paper pags

Method Statement:

Surface prepration

Surface to be tiled should be flat , throughly clean and free from grease , dirt , dust and unsound material .

 $M\ C$ - $Tile\ Weld\ can\ not\ be\ used\ with\ non-porous\ surface$, like painted concrete , plastics, metals or woods .

Mixing

M C - Tile Weld is mixed with water , as the ecommended mixing ratio , and stirred well to achieve the consistency of tilling mortar .

Method of application:

- Use special notched steel trowel with interchangeable blades .
- ◆ Apply an even layer of M C Tile Weld with flat edge of trowel .
- Progressively rib the layer with the notched edge of trowel.
- Apply the tiles while ribs are still wet and tacky so as to secur maximum bond strength.

For more details contact Master Chemicals Technology technical department

Or visit our website www.mc.com.eg

Master Chemicals Technology

11 Ahmed Kamal str, - Heliopolis Tel / Fax : 26244491 / 26244492

Mob: 01001615868