

MASTER CHEMICALS TECHNOLOGY

MC- Deck Seal RE

Rubberized bitumen emulsion

Description:

MC- Deak Seal RE is a ready to use, cold apply bitumen containing rubber.

Uses:

Used for insulating of concrete, wood and steel surfaces against water in under ground construction, swimming pools, and foundations.

Advantages:

- Good insulation.
- Elastic coat resists temperature variations.
- Suitable for dry and damp surfaces.
- Highly chemical resistance.
- Good adhesion on the surfaces.

Technical Data:

Appearance : Brown & black liquid Density : 1.05 ± 0.02 g/cm²

Drying : 2-5 hours

Heat resistance $: (-25^5C) - (90^5C)$

Consumption : $2-4 \text{ m}^2/\text{ kg}$ (depends on the surface)

Shelf life : 12 months

Application:

- Surface should clean and free from oil, grease and dust.
- Applied by brush or spray .
- Stirre the package will before use .
- Primer coat is applied by dilution with 5- 10 % clean water, and then two or three coats are applied.
- Tools can be cleaned with water.

Packaging:

15 Kg Pail or 200 Kg drum.

For more details contact Master Chemicals Technology technical department

Or visit our website www.mc.com.eg

11 Ahmed Kamal str, - Heliopolis Tel / Fax : 26244491 / 26244492 Mob : 01001615868