

MASTER CHEMICALS TECHNOLOGY

MC- Master Back

Concrete Sealant Backing

Description:

MC-Master Back is a closed cell polyethylene backing rod complies with ASTM C 1193 type A . Uses:

Used as sealant backing material for vertical and horizontal concrete joints .

Advantages:

- Easy to use and no need to use bond breaker.
- Controls the depth and shape of sealant in the joint .
- Permits full sealant wetting of the substrate surface when tooled .
- Acts as a temporary joint seal for weather protection when conditions are unsuitable for immediate sealant application
- Suitable to use with most of sealant materials , polyurethane , polysulphide .
- Available with different diameters , from 5 to 50 mm .
- Resists permanent deformation before and during sealant application .
- ♦ Non absorbed liquid water and gas .
- Not emit gas upon mild heating .
- Capable of supporting the sealant in traffic areas .

Method Statement:

Joint preparation:

Joint to receive sealant shall be cleaned out and raked to the full with width and depth required for installation of joint seal materials .

<u>Surface cleaning</u> :

Clean all joints thorouly, removing dust, paints, oils, grease, water and all foreign materials.

<u>Primer</u>:

Prime surfaces when recommended by the sealant manufacturer.

<u>Sealant Backing</u>:

The proper selection and use of sealant backing is important to ensure good function M C - Master Back should be selected with a diameter approximately 25 to 35 % greater than the joint width .

For more details contact Master Chemicals Technology technical department Or visit our website <u>www.mc.com.eg</u>

Master Chemicals Technology

11 Ahmed Kamal str, - Heliopolis Tel / Fax : 26244491 / 26244492 Mob : 01001615868